

IBM TotalStorage N3700



The challenge: Support cost-effective, enterprise-class storage

Corporate workgroups, distributed enterprises and small- to medium-sized companies are increasingly seeking to network and consolidate storage to improve availability, share information, reduce costs, and protect and secure information. These organizations require enterprise-class solutions capable of addressing immediate storage needs cost-effectively, while providing an upgrade path for future requirements. Ideally, IT managers would like a maximum degree of flexibility to design the architecture that best supports the requirements of multiple types of data and a broad range of applications.

Highlights

- **High availability—leverages proven features including a high performing and scalable operating system, data management software and redundancy features**
- **Scalable and upgradeable—supports scalability and rapid upgrades with no required data migration**
- **Heterogeneous storage access—designed to provide networked storage capable of consolidating NAS and iSCSI storage requirements**

The solution: IBM TotalStorage N3700 storage system

IBM TotalStorage® N3700 is designed to offer you fast data access with extremely low maintenance requirements for a highly capable data storage solution. The N3700 filer integrates storage and storage processing into a single unit, facilitating affordable network deployments. These advanced storage systems leverage a proven storage architecture and offer standard IBM TotalStorage N series elements, including integrated I/O, high availability via clustering, and Fibre Channel disk drives. IBM TotalStorage N3700 models are designed to integrate easily into existing IT environments to deliver unified storage for organizations with NAS, iSCSI, or combined environments, making enterprise-level storage a realistic goal for company sites regardless of size or staffing.

Enterprise-class storage based on standard IBM TotalStorage N series architecture

N3700 models use Fibre Channel disk drives as their storage media to support enterprise-class reliability. All N3700 systems are configured with Data ONTAP™ software. Data ONTAP can facilitate greater efficiency and productivity within your organization, which can help reduce the total cost of ownership (TCO).

Scalability to address evolving storage needs

With a purchase price and a scalability model that can help you protect your storage investment, the IBM TotalStorage N3700 offers exceptional value for organizations of all sizes. The N3700 supports low-impact scalability. This is designed to allow you to scale your storage infrastructure to keep pace with growing storage needs without taking mission-critical applications and information offline. The N3700 supports up to 16.8TB of physical capacity, and as storage needs evolve, a simple upgrade process is designed to enable you to easily and quickly upgrade an installed N3700 system.

Highly flexible, unified storage solution

The IBM TotalStorage N3700 offers an excellent solution for a broad range of deployment scenarios. The N3700 supports Ethernet environments, enabling economical NAS and iSCSI deployments. The N3700 system functions as an “unification engine”, which is designed to allow you to simultaneously serve both file and block-level data across a single network—demanding procedures that for some solutions require multiple, separately managed systems. The flexibility of the N3700 allows it to address the storage needs of a wide range of organizations, including distributed enterprises and data centers for midrange enterprises. The N3700 also supports sites with computer and data-intensive enterprise applications such as database, data warehousing, workgroup collaboration and messaging.

Affordable data protection for distributed enterprises

N3700 storage systems can offer significant advantages for distributed enterprises with remote and branch office sites. These organizations and others can leverage the SnapVault® and SnapMirror® software functions to implement a cost-effective data protection strategy by mirroring data back to a corporate data center. N3700 systems can help improve data availability, and simplify backup and restore operations by implementing centralized backup via a single methodology,

which helps reduce tape management requirements and the need for remote systems administration. Recovering data backed up on IBM TotalStorage N3700 systems can be faster and more reliable than recovering from tape.

This solution helps reduce the requirement for sophisticated IT infrastructure and local, resident IT support resources at remote sites, and leverages the advantages of IBM TotalStorage N3700 systems installed at corporate headquarters.

Helps reduced TCO and provide long-term investment protection

N3700 systems support a low TCO with an affordable price point, easy installation and configuration, and ease of ongoing maintenance. Standardization on the IBM TotalStorage N3700 storage architecture can help your organization leverage staff IT skills and reduce complexity. The innovative design of the N3700 results in a smaller form-factor appliance that conserves scarce and valuable space in data centers or remote office locations. In addition, the ability to support unified storage networks allows you to leverage your current network investment while deploying a long-term, highly scalable and easily upgradeable storage solution.

IBM TotalStorage N3700 at a glance

Operating system	IBM TotalStorage N3700 with Data ONTAP™ 7.1 software
Standard software features	Integrated automatic RAID manager, Snapshot™, Fast Boot, telnet, e-mail alerts, NIS, DNS, SNMP, FilerView®, NDMP, SecureAdmin™, FlexVol™
Network protocol support	NFS V2/V3/V4 over UDP or TCP, PCNFSD V1/V2 for (PC) NFS client authentication, Microsoft® CIFS, VLD, FTP, HTTP 1.0, HTTP 1.1 Virtual Hosts
SAN protocol support	iSCSI
Licensed software products	FlexClone™, SnapMirror®, SnapVault®, SnapRestore®, SnapLock™, Clustered Failover, MultiStore®, LockVault™
Hardware features	3U Integrated filer and disk storage available in 19" rack-mount configurations, redundant hot plug power supplies and cooling, 2 integrated full duplex 10/100/1000 Ethernet ports per NAS controller, 2 integrated FC ports per NAS controller, CompactFlash and diagnostic LEDs/OPS
Default/min./max. RAID group sizes	RAID 4—Default: 6 data + 1 parity / Min: 1 data + 1 parity / Max: 13 data + 1 parity RAID DP—Default: 14 data + 2 parity / Max: 26 data + 2 parity (FC)
Disk drive capacities supported	73.4GB 10K and 15K, 146.8GB 10K and 15K, 300GB 10K Fibre Channel disk drives

Filer specifications	N3700 A10	N3700 A20
Max. raw capacity	16.8TB	16.8TB
Max. number of disk drives	56	56
Volumes and RAID groups (min./max. of 1 RAID group per volume)	1/7	1/7
Max. volume size (physical capacity)	8TB	8TB
ECC memory	1GB	2GB
Nonvolatile memory	128MB	256MB
Integrated I/O		
Ethernet 10/100/1000 copper	2	4
Copper FC ports for EXP600 expansion unit attachment	1	2
Optical FC ports for tape attachment	1	2
Clustered failover-capable	No	Yes
Rack Mount (in IBM 2101 Storage Solutions Rack Model 200 or other industry-standard 19-inch rack)	Yes	Yes

Environmental specifications

AC power / max. current	100 to 120VAC, 4 A; 200 to 240VAC, 2 A
Thermal rating	1,215 Btu/hr (fully loaded shelf)
Dimensions (height/width/depth)	3 EIA U (5.25", 13.3 cm) / 19" EIA rack compliant (17.6", 44.7 cm) / 20" (50.8 cm)
Weight (max.)	78.8 lb (35.8 kg) fully loaded
Operating temperature & relative humidity	10°C to 40°C (50°F to 104°F); 10% to 90% relative humidity, non-condensing
Non-operating temperature & relative humidity	-40°C to 65°C (-40° F to 149° F); 10% to 95% relative humidity, non-condensing
Operating acoustic noise	<49 dBA @ 1m at 23°C
Min. service clearances	9" (23 cm) front; 30" (76.2 cm) rear; 3" (7.6 cm) rear for cable radius
Storage sub-system	
Disk drive storage system	Up to 3 EXP600 disk expansion units with 14 low-profile slots for FC disk drives (each)
Disk drive storage interface	Fibre-Channel Arbitrated Loop (FC-AL)
Power supply/cooling fans	Dual, redundant, hot-pluggable, integrated power supply/fan assemblies (220V/110V)

Regulations

Filer safety	EN 60950:2000, CE, UL60950-2000, CSA 60950-00, CB IEC 60950 Ed. 3 (all national deviations), EN60825-1:1994+A11, IRAM, GOST-R
Disk shelf safety	UL/C-UL; CE
Emissions	FCC Class A, EN 55022:1998, EN 61000-3-2, EN 61000-3-3, CE, BSMI, AS/NZ 3548, VCCI
Immunity	EN 55024:1998

N3700 Enterprise Filer supported backup methods

Disk-based backup	SnapVault, SnapMirror
Host-based backup	NDMP/NFS/CIFS/iSCSI
GbE-attached tape support	ibm.com /totalstorage/nas, refer to TotalStorage N series interoperability matrix
Direct-attached tape support	ibm.com /totalstorage/nas, refer to TotalStorage N series interoperability matrix
SAN-attached tape support	ibm.com /totalstorage/nas, refer to TotalStorage N series interoperability matrix
iSCSI initiator, IP fabric and host attached support	ibm.com /totalstorage/nas, refer to TotalStorage N series interoperability matrix

For more information

Contact your IBM representative or
IBM Business Partner or visit:

ibm.com/totalstorage/nas/



© Copyright IBM Corporation 2005

IBM Systems and Technology Group
5600 Cottle Road
San Jose, CA 95193
U.S.A.

Produced in the United States
July 2005
All Rights Reserved

IBM, the IBM logo, and TotalStorage are trademarks or registered trademarks of International Business Machines Corporation in the United States, other countries or both.

FilerView, MultiStore, SnapMirror, SnapRestore and SnapVault are registered trademarks and Data ONTAP, FlexClone, LockVault, SecureAdmin, SnapLock and SnapShot are trademarks of Network Appliance, Inc., in the U.S. and other countries.

LTO is a trademark of IBM, Hewlett Packard and Certance in the United States, other countries, or both.

Microsoft, Windows, Windows NT and Windows Server are trademarks or registered trademarks of Microsoft Corporation in the United States, other countries or both.

Other company, product and service names may be trademarks or service marks of others.

This document could include technical inaccuracies or typographical errors. IBM may make changes, improvements or alterations to the products, programs and services described in this document, including termination of such products, programs and services, at any time and without notice. Any statements regarding IBM's future direction and intent are subject to change or withdrawal without notice, and represent goals and objectives only. The information contained in this document is current as of the initial date of publication only and is subject to change without notice. IBM shall have no responsibility to update such information.

IBM is not responsible for the performance or interoperability of any non-IBM products discussed herein. Performance data for IBM and non-IBM products and services contained in this document was derived under specific operating and environmental conditions. The actual results obtained by any party implementing such products or services will depend on a large number of factors specific to such party's operating environment and may vary significantly. IBM makes no representation that these results can be expected or obtained in any implementation of any such products or services.

MB, GB and TB equal 1,000,000, 1,000,000,000 and 1,000,000,000,000 bytes, respectively, where referring to storage capacity. Actual storage capacity will vary based upon many factors and may be less than stated. Some numbers given for storage capacities give capacity in native mode followed by capacity using data compression technology.

THE INFORMATION IN THIS DOCUMENT IS PROVIDED "AS-IS" WITHOUT ANY WARRANTY, EITHER EXPRESSED OR IMPLIED. IBM EXPRESSLY DISCLAIMS ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NONINFRINGEMENT. IBM products are warranted according to the terms and conditions of the agreements (e.g., IBM Customer Agreement, Statement of Limited Warranty, International Program License Agreement, etc.) under which they are provided.

References in this document to IBM products, programs or services do not imply that IBM intends to make such products, programs or services available in all countries in which IBM operates or does business. Any reference to an IBM program or product in this document is not intended to state or imply that only that program may be used. Any functionally equivalent program or product that does not infringe IBM's intellectual property rights may be used instead. It is the user's responsibility to evaluate and verify the operation of any non-IBM product, program or service.

